

ALS Technichem (HK) Pty Ltd

11/F., Chung Shun Knitting Centre,

1 - 3 Wing Yip Street,

Kwai Chung, N.T., Hong Kong **T:** +852 2610 1044

F: +852 2610 2021 www.alsglobal.com

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

CONTACT: MR K.W. FAN WORK ORDER: HK2437680

CLIENT: ENVIROTECH SERVICES CO.

ADDRESS: RM 712, 7/F, MY LOFT SUB-BATCH: (

9 HOI WING ROAD,
TUEN MUN, N.T. HK

DATE RECEIVED:
17-Sep-2024
DATE OF ISSUE:
30-Sep-2024

GENERAL COMMENTS

The performance of the equipment stated in this report is checked with independent reference material and results compared against a calibrated secondary source.

The "Tolerance Limit" quoted is the acceptance criteria applicable for similar equipment used by the laboratory or quoted from relevant international standards.

The "Next Calibration Date" is recommended according to best practice principle as practised by the laboratory or quoted from relevant international standards.

The validity of equipment/ meter performance only applies to the result(s) stated in the report.

This report superseded any previous report(s) with same work order number.

EQUIPMENT INFORMATION

Equipment information (Brand name, Model No., Serial No. and Equipment No.) is provided by client.

Equipment Type: Multifunctional Meter Service Nature: Performance Check

Scope: Conductivity, Dissolved Oxygen, Turbidity, Salinity and Temperature

Brand Name/ Model No.: [HORIBA]/ [U-53]
Serial No./ Equipment No.: [FXMONLLF]/ [N/A]
Date of Calibration: 23-September-2024

16:5

Ms. Lin Wai Yu, Iris Assistant Manager - Inorganics

This report may not be reproduced except with prior written approval from ALS Technichem (HK) Pty Ltd.

WORK ORDER: HK2437680

SUB-BATCH: 0

DATE OF ISSUE: 30-Sep-2024

CLIENT: ENVIROTECH SERVICES CO.

Equipment Type:

Multifunctional Meter

Brand Name/

[HORIBA]/[U-53]

Model No.: Serial No./

[FXMONLLF]/ [N/A]

Equipment No.:

Date of Calibration: 23-September-2024

Date of Next Calibration: 23-December-2024

PARAMETERS:

Conductivity Method Ref: APHA (23rd edition), 2510B

ſ	Expected Reading (μS/cm)	Displayed Reading (μS/cm)	Tolerance (%)
	146.9	159	+8.2
	6667	6980	+4.7
	12890	13200	+2.4
	58670	58700	+0.1
		Tolerance Limit (%)	±10.0

Dissolved Oxygen

Method Ref: APHA (23rd edition), 4500O: G

Expected Reading (mg/L)	Displayed Reading (mg/L)	Tolerance (mg/L)
2.88	2.79	-0.09
4.59	4.54	-0.05
7.00	6.85	-0.15
	Tolerance Limit (mg/L)	±0.20

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris

Assistant Manager - Inorganics

WORK ORDER: HK2437680

SUB-BATCH: 0

DATE OF ISSUE: 30-Sep-2024

CLIENT: ENVIROTECH SERVICES CO.

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[HORIBA]/[U-53]

Serial No./

[FXMONLLF]/[N/A]

Equipment No.: Date of Calibration:

23-September-2024 Date of Next Calibration:

23-December-2024

PARAMETERS:

Turbidity Method Ref: APHA (23rd edition), 2130B

Expected Reading (NTU)	Displayed Reading (NTU)	Tolerance (%)
0	0.38	
4	3.65	-8.8
40	42.1	+5.3
80	79.4	-0.7
400	416	+4.0
800	818	+2.3
	Tolerance Limit (%)	±10.0

Salinity Method Ref: APHA (23rd edition), 2520B

Expected Reading (ppt)	Displayed Reading (ppt)	Tolerance (%)
0	0.01	
10	10.22	+2.2
20	19.85	-0.7
30	30.26	+0.9
	Tolerance Limit (%)	±10.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris

Assistant Manager - Inorganics

WORK ORDER: HK2437680

SUB-BATCH: 0

DATE OF ISSUE: 30-Sep-2024

CLIENT: ENVIROTECH SERVICES CO.

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[HORIBA]/[U-53]

Serial No./

[FXMONLLF]/[N/A]

Equipment No.:
Date of Calibration:

23-September-2024

23-December-2024

PARAMETERS:

Temperature

Method Ref: Section 6 of International Accreditation New Zealand Technical

Guide No. 3 Second edition March 2008: Working Thermometer Calibration Procedure.

Date of Next Calibration:

Expected Reading (°C)	Displayed Reading (°C)	Tolerance (°C)
11.5	13.25	+1.8
19.0	18.74	-0.3
39.5	38.15	-1.4
	Tolerance Limit (°C)	±2.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris

Assistant Manager - Inorganics



ALS Technichem (HK) Pty Ltd

11/F., Chung Shun Knitting Centre,

1 - 3 Wing Yip Street,

Kwai Chung, N.T., Hong Kong

T: +852 2610 1044 F: +852 2610 2021 www.alsglobal.com

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

CONTACT: MR K.W. FAN WORK ORDER: HK2444040

CLIENT: ENVIROTECH SERVICES CO.

ADDRESS: RM 712, 7/F, MY LOFT SUB-BATCH: (

9 HOI WING ROAD,
TUEN MUN, N.T. HK
DATE RECEIVED: 25-Oct-2024
DATE OF ISSUE: 12-Nov-2024

GENERAL COMMENTS

The performance of the equipment stated in this report is checked with independent reference material and results compared against a calibrated secondary source.

The "Tolerance Limit" quoted is the acceptance criteria applicable for similar equipment used by the laboratory or quoted from relevant international standards.

The "Next Calibration Date" is recommended according to best practice principle as practised by the laboratory or quoted from relevant international standards.

The validity of equipment/ meter performance only applies to the result(s) stated in the report.

This report superseded any previous report(s) with same work order number.

EQUIPMENT INFORMATION

Equipment information (Brand name, Model No., Serial No. and Equipment No.) is provided by client.

Equipment Type: Multifunctional Meter Service Nature: Performance Check

Scope: Conductivity, Dissolved Oxygen, Turbidity, Salinity and Temperature

Brand Name/ Model No.: [HORIBA]/ [U-53]
Serial No./ Equipment No.: [KP23RRSM]/ [N/A]
Date of Calibration: 04-November-2024

 \mathcal{M}

Ms. Cheng Sin Ying, May Senior Chemist - Inorganics

This report shall not be reproduced except in full without the written approval of the laboratory.

WORK ORDER: HK2444040

SUB-BATCH:

0

DATE OF ISSUE:

12-Nov-2024

CLIENT:

ENVIROTECH SERVICES CO.

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[HORIBA]/[U-53]

Serial No./

[KP23RRSM]/[N/A]

Equipment No.: Date of Calibration:

04-November-2024

Date of Next Calibration:

04-February-2025

PARAMETERS:

Conductivity

Method Ref: APHA (23rd edition), 2510B

Expected Reading (µS/cm)	Displayed Reading (μS/cm)	Tolerance (%)
146.9	148	+0.7
6667	6510	-2.4
12890	12600	-2.2
58670	57900	-1.3
	Tolerance Limit (%)	+10.0

Dissolved Oxygen

Method Ref: APHA (23rd edition), 4500O: G

Expected Reading (mg/L)	Displayed Reading (mg/L)	Tolerance (mg/L)
2.18	2.29	+0.11
5.45	5.40	-0.05
7.69	7.53	-0.16
	Tolerance Limit (mg/L)	±0.20

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Man

WORK ORDER: HK2444040

SUB-BATCH: 0

DATE OF ISSUE: 12-Nov-2024

CLIENT: ENVIROTECH SERVICES CO.

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[HORIBA]/[U-53]

Serial No./ Equipment No.:

[KP23RRSM]/[N/A]

Date of Calibration:

04-November-2024

Date of Next Calibration:

04-February-2025

PARAMETERS:

Turbidity Method Ref: APHA (23rd edition), 2130B

Expected Reading (NTU)	Displayed Reading (NTU)	Tolerance (%)
0	0.00	
4	3.94	-1.5
40	38.3	-4.3
80	82.8	+3.5
400	383	-4.3
800	793	-0.9
	Tolerance Limit (%)	±10.0

Salinity Method Ref: APHA (23rd edition), 2520B

Expected Reading (ppt)	Displayed Reading (ppt)	Tolerance (%)
0	0.00	
10	9.55	-4.5
20	19.28	-3.6
30	29.09	-3.0
	Tolerance Limit (%)	±10.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Man

WORK ORDER: HK2444040

SUB-BATCH: 0

DATE OF ISSUE: 12-Nov-2024

CLIENT: ENVIROTECH SERVICES CO.

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[HORIBA]/[U-53]

Serial No./ Equipment No.:

[KP23RRSM]/[N/A]

Date of Calibration:

04-November-2024

Date of Next Calibration:

04-February-2025

PARAMETERS:

Temperature Method Ref: Section 6 of International Accreditation New Zealand Technical

Guide No. 3 Second edition March 2008: Working Thermometer Calibration Procedure.

Expected Reading (°C)	Displayed Reading (°C)	Tolerance (°C)
10.0	11.24	+1.2
20.0	19.73	-0.3
39.0	37.50	-1.5
	Tolerance Limit (°C)	±2.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Man



ALS Technichem (HK) Pty Ltd

11/F., Chung Shun Knitting Centre,

1 - 3 Wing Yip Street,

Kwai Chung, N.T., Hong Kong

T: +852 2610 1044 F: +852 2610 2021 www.alsglobal.com

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

CONTACT: MR IVAN LEUNG WORK ORDER: HK2447140

CLIENT: ALS TECHNICHEM (HK) PTY LTD

ADDRESS: 11/F., CHUNG SHUN KNITTING CENTRE, SUB-BATCH: (

1-3 WING YIP STREET, KWAI CHUNG, N.T. LABORATORY: HONG KONG

DATE RECEIVED: 12-Nov-2024 **DATE OF ISSUE:** 15-Nov-2024

GENERAL COMMENTS

The performance of the equipment stated in this report is checked with independent reference material and results compared against a calibrated secondary source.

The "Tolerance Limit" quoted is the acceptance criteria applicable for similar equipment used by the laboratory or quoted from relevant international standards.

The "Next Calibration Date" is recommended according to best practice principle as practised by the laboratory or quoted from relevant international standards.

The validity of equipment/ meter performance only applies to the result(s) stated in the report.

This report superseded any previous report(s) with same work order number.

EQUIPMENT INFORMATION

Equipment information (Brand name, Model No., Serial No. and Equipment No.) is provided by client.

Equipment Type: pH meter

Service Nature: Performance Check

Scope: pH Value and Temperature

Brand Name/ Model No.: [LUTRON]/ [PH-208]

Serial No./ Equipment No.: [AL.59355/TF31039]/ [HK2141]

Date of Calibration: 14-November-2024

NAM

Ms. Cheng Sin Ying, May Senior Chemist - Inorganics

This report shall not be reproduced except in full without the written approval of the laboratory.

WORK ORDER: HK2447140

SUB-BATCH: 0

15-Nov-2024

DATE OF ISSUE: CLIENT: ALS TECHNICHEM (HK) PTY LTD

Equipment Type:

pH meter

Brand Name/

[LUTRON]/[PH-208]

Model No.: Serial No./

[AL.59355/TF31039]/[HK2141]

Equipment No.: Date of Calibration:

14-November-2024

Date of Next Calibration:

14-February-2025

PARAMETERS:

pH Value Method Ref: APHA (23rd edition), 4500H: B

Expected Reading (pH unit)	Displayed Reading (pH unit)	Tolerance (pH unit)
4.0	3.93	-0.07
7.0	7.03	+0.03
10.0	10.01	+0.01
	Tolerance Limit (pH unit)	±0.20

Temperature

Method Ref: Section 6 of International Accreditation New Zealand Technical

Guide No. 3 Second edition March 2008: Working Thermometer Calibration Procedure.

Expected Reading (°C)	Displayed Reading (°C)	Tolerance (°C)
11.0	11.9	+0.9
19.0	19.1	+0.1
38.5	38.3	-0.2
	Tolerance Limit (°C)	±2.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.